

**HK2210**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Technical information



Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	22 mm	Under roller diameter
D	28 mm	Outside diameter
C	10 mm	Width
C_r	7.500 N	Basic dynamic load rating, radial
C_{0r}	10.500 N	Basic static load rating, radial
C_{ur}	1.390 N	Fatigue load limit, radial
n_G	11.700 1/min	Limiting speed
n_G Grease	7.000 1/min	Limiting speed for grease lubrication
n_{gr}	9.000 1/min	Reference speed
$\approx m$	12,148 g	Weight

Dimensions

C_1	10 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	140 °C	Operating temperature max.

Additional information

SD22X28X4	Sealing ring
G22X28X4	Sealing ring 2

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope