

**HK2816**

## Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

## Technical information



## Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

## Main Dimensions &amp; Performance Data

$F_w$	28 mm	Under roller diameter
D	35 mm	Outside diameter
C	16 mm	Width
$C_r$	16.400 N	Basic dynamic load rating, radial
$C_{0r}$	26.500 N	Basic static load rating, radial
$C_{ur}$	3.500 N	Fatigue load limit, radial
$n_G$	9.200 1/min	Limiting speed
$n_{G \text{ Grease}}$	5.500 1/min	Limiting speed for grease lubrication
$n_{gr}$	6.800 1/min	Reference speed
$\approx m$	28,48 g	Weight

## Dimensions

$C_1$	16 mm	Width, outer ring
$r_{\min}$	0,8 mm	Minimum chamfer dimension








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

### Additional information

SD28X35X4	Sealing ring
G28X35X4	Sealing ring 2
IR22X28X17-XL	Suitable inner rings IR

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope