

**HK3220**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Technical information



Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F_w	32 mm	Under roller diameter
D	39 mm	Outside diameter
C	20 mm	Width
C_r	23.000 N	Basic dynamic load rating, radial
C_{0r}	42.500 N	Basic static load rating, radial
C_{ur}	5.600 N	Fatigue load limit, radial
n_G	8.100 1/min	Limiting speed
n_G Grease	4.850 1/min	Limiting speed for grease lubrication
n_{gr}	5.900 1/min	Reference speed
$\approx m$	41,068 g	Weight

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	140 °C	Operating temperature max.

Additional information

IR28X32X20-XL	Suitable inner rings IR
---------------	-------------------------

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope