

**HK4020-RR**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end
HK...RR, single row, with cage

Technical information



Your current product variant

Lubricant	Without	
Lubrication hole	Without	
Coating	RR	Protected against corrosion by Corrotect special coating
Sealing	Without	

Main Dimensions & Performance Data

F_w	40 mm	Under roller diameter
D	47 mm	Outside diameter
C	20 mm	Width
C_r	25.500 N	Basic dynamic load rating, radial
C_{0r}	52.000 N	Basic static load rating, radial
C_{ur}	6.900 N	Fatigue load limit, radial
n_G	6.600 1/min	Limiting speed
n_G Grease	3.950 1/min	Limiting speed for grease lubrication
n_{gr}	4.900 1/min	Reference speed
m	50 g	Weight

Dimensions

C_1	20 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

SD40X47X4	Sealing ring
G40X47X4	Sealing ring 2
LR35X40X20,5	Suitable inner rings LR
IR35X40X20,5-XL	Suitable inner rings IR