


**HK1814-RS**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK..-RS, lip seal on one side, to DIN 618

Technical information

**Your current product variant**

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Type of Seal	RS	Contact seal on one sides

Main Dimensions & Performance Data

F_w	18 mm	Under roller diameter
D	24 mm	Outside diameter
C	14 mm	Width
C_r	8.100 N	Basic dynamic load rating, radial
C_{0r}	10.900 N	Basic static load rating, radial
C_{ur}	1.330 N	Fatigue load limit, radial
n_G	8.400 1/min	Limiting speed
n_G Grease	8.400 1/min	Limiting speed for grease lubrication
m	14,286 g	Weight

Dimensions

r_{min}	0,8 mm	Minimum chamfer dimension
-----------	--------	---------------------------

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.



Additional information

LR15X18X16,5

Suitable inner rings LR

IR15X18X16-XL

Suitable inner rings IR

Characteristics



Radial load



Grease Lubrication



Sealed on one side



Small design envelope