

**HK0908-B-L271** [↗](#)

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Technical information



Your current product variant

Lubricant	L271	Grease (L271/standart specific)
Lubrication hole	Without	
Coating	Without	
Sealing	Without	

Main Dimensions & Performance Data

F_w	9 mm	Under roller diameter
D	13 mm	Outside diameter
C	8 mm	Width
C_r	3.550 N	Basic dynamic load rating, radial
C_{0r}	3.750 N	Basic static load rating, radial
C_{ur}	450 N	Fatigue load limit, radial
n_G	26.500 1/min	Limiting speed
$n_{G \text{ Grease}}$	16.000 1/min	Limiting speed for grease lubrication
n_{gr}	20.600 1/min	Reference speed
$\approx m$	3,04 g	Weight

Dimensions

C_1	8 mm	Width, outer ring
r_{\min}	0,4 mm	Minimum chamfer dimension








Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	140 °C	Operating temperature max.

Additional information

GR9X13X3	Sealing ring
G9X13X3	Sealing ring 2

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope