


**HK2818-RS**

## Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK..-RS, lip seal on one side, to DIN 618

## Technical information



## Your current product variant

Coating	Without	
Sealing	RS	Contact seal on one sides

## Main Dimensions &amp; Performance Data

$F_w$	28 mm	Under roller diameter
D	35 mm	Outside diameter
C	18 mm	Width
$C_r$	16.400 N	Basic dynamic load rating, radial
$C_{0r}$	26.500 N	Basic static load rating, radial
$C_{ur}$	3.500 N	Fatigue load limit, radial
$n_G$	5.500 1/min	Limiting speed
$n_G$ Grease	5.500 1/min	Limiting speed for grease lubrication
$m$	31 g	Weight

## Dimensions

$r_{min}$	0,8 mm	Minimum chamfer dimension
-----------	--------	---------------------------

## Temperature range

$T_{min}$	-20 °C	Operating temperature min.
$T_{max}$	100 °C	Operating temperature max.







### Additional information

---

LR22X28X20,5	Suitable inner rings LR
IR22X28X20-XL	Suitable inner rings IR

### Characteristics

---

-  Radial load
-  Grease Lubrication
-  Sealed on one side
-  Small design envelope