


**HN1212-L077** [↗](#)

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HN, full complement needle roller set

## Technical information

**Your current product variant**

Lubricant	L077	Grease (L077/customer specific)
-----------	------	---------------------------------

**Main Dimensions & Performance Data**

$F_w$	12 mm	Under roller diameter
$D$	18 mm	Outside diameter
$C$	12 mm	Width, outer ring
$C_r$	10.200 N	Basic dynamic load rating, radial
$C_{0r}$	15.200 N	Basic static load rating, radial
$C_{ur}$	1.990 N	Fatigue load limit, radial
$n_G$ Grease	8.600 1/min	Limiting speed for grease lubrication
$n_{gr}$	12.000 1/min	Reference speed
$m$	11 g	Weight

**Dimensions**

$r_{min}$	0,8 mm	Minimum chamfer dimension
-----------	--------	---------------------------

**Temperature range**

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

**Additional information**

IR8X12X12,5-XL	Suitable inner rings IR
LR8X12X12,5	Suitable inner rings LR



### Characteristics

---

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope