

**NA4826-XL-C3**

## Needle roller bearing

Needle roller bearing NA..-XL, single row,  
with inner ring, outer ring with 2 bords

X-life

## Technical information



## Your current product variant

Cage	Standard	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Coating	Without	

## Main Dimensions &amp; Performance Data

d	130 mm	Bore diameter
D	165 mm	Outside diameter
B	35 mm	Width
C <sub>r</sub>	134.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	310.000 N	Basic static load rating, radial
C <sub>ur</sub>	49.500 N	Fatigue load limit, radial
n <sub>G</sub>	3.250 1/min	Limiting speed
n <sub>gr</sub>	1.930 1/min	Reference speed
≈m	1,782 kg	Weight

## Dimensions

F	145 mm	Raceway diameter inner ring
r <sub>min</sub>	1,1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement



### Temperature range

---

$T_{\min}$  -30 °C Operating temperature min.

$T_{\max}$  120 °C Operating temperature max.

### Characteristics

---



Radial load



Grease Lubrication



Oil Lubrication



Not sealed



Small design envelope