

**NA4905-XL-C3**

## Needle roller bearing

Needle roller bearing NA49...-XL, single row, with inner ring, outer ring with 2 bords

X-life

## Technical information



## Your current product variant

Cage	Standard	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Coating	Without	

## Main Dimensions &amp; Performance Data

d	25 mm	Bore diameter
D	42 mm	Outside diameter
B	17 mm	Width
C <sub>r</sub>	26.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	31.500 N	Basic static load rating, radial
C <sub>ur</sub>	5.800 N	Fatigue load limit, radial
n <sub>G</sub>	14.400 1/min	Limiting speed
n <sub>gr</sub>	7.700 1/min	Reference speed
≈m	90,15 g	Weight

## Dimensions

F	30 mm	Raceway diameter inner ring
r <sub>min</sub>	0,3 mm	Minimum chamfer dimension
s	0,8 mm	Axial displacement



### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope