

**NA6906-XL-C3**

## Needle roller bearing

Needle roller bearing NA69...-XL, single row,  
with inner ring, outer ring with 2 bords

X-life

## Technical information



## Your current product variant

Cage	Standard	
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Coating	Without	

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	47 mm	Outside diameter
B	30 mm	Width
$C_r$	49.000 N	Basic dynamic load rating, radial
$C_{0r}$	71.000 N	Basic static load rating, radial
$C_{ur}$	13.100 N	Fatigue load limit, radial
$n_G$	12.600 1/min	Limiting speed
$n_{gr}$	6.300 1/min	Reference speed
$m$	185,7 g	Weight

## Dimensions

F	35 mm	Raceway diameter inner ring
$r_{min}$	0,3 mm	Minimum chamfer dimension
s	1 mm	Axial displacement



### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-   $F_r$  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope