


**NK30/20-F-XL**

## Needle roller bearing

Needle roller bearing NK..-F-XL, single row,  
no inner ring, outer ring with 2 bords

X-life

## Technical information



## Your current product variant

Lubricant	Without	
Cage	F	Cage of steel
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

## Main Dimensions &amp; Performance Data

$F_w$	30 mm	Under roller diameter
D	40 mm	Outside diameter
C	20 mm	Width, outer ring
$C_r$	25.500 N	Basic dynamic load rating, radial
$C_{0r}$	36.000 N	Basic static load rating, radial
$C_{ur}$	6.400 N	Fatigue load limit, radial
$n_G$	14.800 1/min	Limiting speed
$n_{gr}$	8.900 1/min	Reference speed
$\approx m$	63,75 g	Weight

## Dimensions

$r_{min}$	0,3 mm	Minimum chamfer dimension
-----------	--------	---------------------------








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

G45X55X4	Sealing ring
SD45X55X4	Sealing ring 2

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope