

**NK45/20-F-XL**

Needle roller bearing

Needle roller bearing NK..-F-XL, single row,
no inner ring, outer ring with 2 bords

X-life

Technical information



Your current product variant

Lubricant	Without	
Cage	F	Cage of steel
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

Main Dimensions & Performance Data

F_w	45 mm	Under roller diameter
D	55 mm	Outside diameter
C	20 mm	Width, outer ring
C_r	31.000 N	Basic dynamic load rating, radial
C_{0r}	53.000 N	Basic static load rating, radial
C_{ur}	9.400 N	Fatigue load limit, radial
n_G	10.200 1/min	Limiting speed
n_{gr}	6.200 1/min	Reference speed
$\approx m$	90,2 g	Weight

Dimensions

r_{min}	0,3 mm	Minimum chamfer dimension
-----------	--------	---------------------------








Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

G45X55X4	Sealing ring
SD45X55X4	Sealing ring 2

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope