

**NK50/25-F-XL-2S**

Needle roller bearing

Needle roller bearing NK..-F-XL, single row,
no inner ring, outer ring with 2 bords

X-life

Technical information



Your current product variant

Lubricant	Without	
Cage	F	Cage of steel
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

Main Dimensions & Performance Data

F_w	50 mm	Under roller diameter
D	62 mm	Outside diameter
C	25 mm	Width, outer ring
C_r	43.000 N	Basic dynamic load rating, radial
C_{0r}	74.000 N	Basic static load rating, radial
C_{ur}	12.900 N	Fatigue load limit, radial
n_G	9.200 1/min	Limiting speed
n_{gr}	5.700 1/min	Reference speed
m	0,157 kg	Weight

Dimensions

r_{min}	0,6 mm	Minimum chamfer dimension
-----------	--------	---------------------------








Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

G50X62X5	Sealing ring
SD50X62X5	Sealing ring 2

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope