
**RNAO10X17X10-TV-XL**

Needle roller bearing

Needle roller bearings RNAO, without ribs

X-life

## Technical information



## Your current product variant

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------



## Main Dimensions &amp; Performance Data

$F_w$	10 mm	Under roller diameter
D	17 mm	Outside diameter
C	10 mm	Width, outer ring
$C_r$	5.300 N	Basic dynamic load rating, radial
$C_{0r}$	5.500 N	Basic static load rating, radial
$C_{ur}$	940 N	Fatigue load limit, radial
$n_G$	29.500 1/min	Limiting speed
$n_{gr}$	28.000 1/min	Reference speed

$m$	8,8 g	Weight
-----	-------	--------

## Mounting dimensions

$D_b$	10,3 mm	Shoulder diameter axial guidance NK/housing
$d_b$	12,7 mm	Shoulder diameter axial guidance NK/shaft
$D_a$	13,3 mm	Shoulder diameter outer ring
$r_{a \max}$	0,3 mm	Maximum recess radius










### Dimensions

E	13 mm	Raceway diameter outer ring
r <sub>min</sub>	0,3 mm	Minimum chamfer dimension

### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope