

**FAG****KLL365348-LL365310** [↗](#)

## Tapered roller bearing

Tapered roller bearings K-Series, in inch sizes, separable

## Technical information

## Your current product variant

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	384,175 mm	Bore diameter
D	441,325 mm	Outside diameter
B	28,575 mm	Width, inner ring
C	20,638 mm	Width, outer ring
T	28,575 mm	Width, total
$C_r$	250.000 N	Basic dynamic load rating, radial
$C_{0r}$	670.000 N	Basic static load rating, radial
$C_{ur}$	56.000 N	Fatigue load limit, radial
$n_G$	1.580 1/min	Limiting speed
$n_{gr}$	700 1/min	Thermal speed rating
$\approx m$	6,3 kg	Weight





### Mounting dimensions

$d_{a \max}$	393 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	398 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	427 mm	Minimum diameter of housing shoulder
$D_{a \max}$	428 mm	Maximum diameter of housing shoulder
$D_{b \min}$	433 mm	Minimum diameter of housing shoulder
$C_{a \min}$	6 mm	Minimum axial space
$C_{b \min}$	8 mm	Minimum axial space
$r_{a \max}$	3,6 mm	Maximum fillet radius of shaft
$r_{b \max}$	3,3 mm	Maximum fillet radius of housing

### Dimensions

$r_{1, 2 \min}$	3,6 mm	Minimum chamfer dimension of inner ring back face
$r_{3, 4 \min}$	3,3 mm	Minimum chamfer dimension of outer ring back face
$a$	59 mm	Distance between the apexes of the pressure cones
$d_1$	411 mm	Guidance rib diameter of inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,34	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y$	1,76	Dynamic axial load factor
$Y_0$	0,97	Static axial load factor



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed