



FAG

**23132-E1-XL-K-TVPB**

## Spherical Roller Bearing

Spherical roller bearings 231...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

## Technical information



## Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	TVPB	Plastic cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	160 mm	Bore diameter
D	270 mm	Outside diameter
B	86 mm	Width
$C_r$	1.160.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.550.000 N	Basic static load rating, radial
$C_{ur}$	166.000 N	Fatigue load limit, radial
$n_G$	2.490 1/min	Limiting speed
$n_{gr}$	1.560 1/min	Reference speed
$\approx m$	18,349 kg	Weight



### Mounting dimensions

$d_{a \min}$	172 mm	Minimum diameter shaft shoulder
$D_{a \max}$	258 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
$B_{a \min}$	8 mm	Minimum cavity width of the sleeve
$d_{a \max}$	183 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	170 mm	Minimum cavity diameter of the sleeve

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	238,3 mm	Bore diameter outer ring
$d_2$	183,2 mm	Raceway diameter of the inner ring
$d_s$	8 mm	Diameter lubrication hole
$n_s$	15 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$e$	0,29	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,32	Dynamic axial load factor
$Y_2$	3,45	Dynamic axial load factor
$Y_0$	2,26	Static axial load factor

### Additional information

H3132	Adapter sleeve
AH3132A	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment