



## Technical information



### Your current product variant

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E1           | Without central rip               |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | TVPB         | Plastic cage                      |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication             | Standard     |                                   |

### Main Dimensions & Performance Data

|          |             |                                   |
|----------|-------------|-----------------------------------|
| d        | 180 mm      | Bore diameter                     |
| D        | 300 mm      | Outside diameter                  |
| B        | 96 mm       | Width                             |
| $C_r$    | 1.420.000 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 1.950.000 N | Basic static load rating, radial  |
| $C_{ur}$ | 199.000 N   | Fatigue load limit, radial        |
| $n_G$    | 2.230 1/min | Limiting speed                    |
| $n_{gr}$ | 1.350 1/min | Reference speed                   |
| $m$      | 25,963 kg   | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 194 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 286 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,5 mm | Maximum recess radius                |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 3 mm     | Minimum chamfer dimension          |
| $D_1$      | 264,8 mm | Bore diameter outer ring           |
| $d_2$      | 204,1 mm | Raceway diameter of the inner ring |
| $d_s$      | 8 mm     | Diameter lubrication hole          |
| $n_s$      | 15 mm    | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |  |
|-------|------|--|
| $e$   | 0,29 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,32 | Dynamic axial load factor  |
| $Y_2$ | 3,45 | Dynamic axial load factor  |
| $Y_0$ | 2,26 | Static axial load factor   |



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment