



FAG

23226-E1-XL-K-TVPB

Spherical Roller Bearing

Spherical roller bearings 232...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Technical information



Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	TVPB	Plastic cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	230 mm	Outside diameter
B	80 mm	Width
C_r	910.000 N	Basic dynamic load rating, radial
C_{0r}	1.150.000 N	Basic static load rating, radial
C_{ur}	91.000 N	Fatigue load limit, radial
n_G	2.850 1/min	Limiting speed
n_{gr}	1.740 1/min	Reference speed
$\approx m$	12,894 kg	Weight



Mounting dimensions

$d_{a \min}$	144 mm	Minimum diameter shaft shoulder
$D_{a \max}$	216 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$B_{a \min}$	21 mm	Minimum cavity width of the sleeve
$d_{a \max}$	150 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	142 mm	Minimum cavity diameter of the sleeve

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
D_1	199,3 mm	Bore diameter outer ring
d_2	150 mm	Raceway diameter of the inner ring
d_s	4,8 mm	Diameter lubrication hole
n_s	9,5 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,07	Dynamic axial load factor
Y_2	3,09	Dynamic axial load factor
Y_0	2,03	Static axial load factor

Additional information

H2326	Adapter sleeve
AHX3226G	Withdrawal sleeve



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment