



FAG

23232-E1-XL-K-TVPB

Spherical Roller Bearing

Spherical roller bearings 232...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Technical information



Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	TVPB	Plastic cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	Standard	

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	104 mm	Width
C_r	1.460.000 N	Basic dynamic load rating, radial
C_{0r}	1.910.000 N	Basic static load rating, radial
C_{ur}	150.000 N	Fatigue load limit, radial
n_G	2.210 1/min	Limiting speed
n_{gr}	1.280 1/min	Reference speed
$\approx m$	27,533 kg	Weight



Mounting dimensions

$d_{a \min}$	174 mm	Minimum diameter shaft shoulder
$D_{a \max}$	276 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$B_{a \min}$	18 mm	Minimum cavity width of the sleeve
$d_{a \max}$	186 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	174 mm	Minimum cavity diameter of the sleeve

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
D_1	249,3 mm	Bore diameter outer ring
d_2	186,7 mm	Raceway diameter of the inner ring
d_s	8 mm	Diameter lubrication hole
n_s	15 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

e	0,34	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2	Dynamic axial load factor
Y_2	2,98	Dynamic axial load factor
Y_0	1,96	Static axial load factor

Additional information

H2332	Adapter sleeve
AH3232G	Withdrawal sleeve



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment