



## Technical information



### Your current product variant

|                           |              |                           |
|---------------------------|--------------|---------------------------|
| Design                    | E1           | Without central rip       |
| Bore type                 | Z            | Cylindrical               |
| Cage                      | TVPB         | Plastic cage              |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication facility    | Standard     |                           |



### Main Dimensions & Performance Data

|          |             |                                   |
|----------|-------------|-----------------------------------|
| d        | 90 mm       | Bore diameter                     |
| D        | 160 mm      | Outside diameter                  |
| B        | 52,4 mm     | Width                             |
| $C_r$    | 445.000 N   | Basic dynamic load rating, radial |
| $C_{0r}$ | 520.000 N   | Basic static load rating, radial  |
| $C_{ur}$ | 50.000 N    | Fatigue load limit, radial        |
| $n_G$    | 4.250 1/min | Limiting speed                    |
| $n_{gr}$ | 2.650 1/min | Reference speed                   |
| $m$      | 4,228 kg    | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 101 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 149 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2 mm   | Maximum recess radius                |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 2 mm     | Minimum chamfer dimension          |
| $D_1$      | 140 mm   | Bore diameter outer ring           |
| $d_2$      | 104,1 mm | Raceway diameter of the inner ring |
| $d_s$      | 3,2 mm   | Diameter lubrication hole          |
| $n_s$      | 6,5 mm   | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |  |
|-------|------|--|
| $e$   | 0,31 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,2  | Dynamic axial load factor  |
| $Y_2$ | 3,27 | Dynamic axial load factor  |
| $Y_0$ | 2,15 | Static axial load factor   |



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment