



FAG

**22340-BE-XL-K-JPA-T41A** [↗](#)

## Spherical Roller Bearing

Spherical roller bearings 223...E1-K-T41A,  
For oscillating load with restricted diameter  
tolerances, with tapered bore

X-life

## Technical information



## Your current product variant

|  |              |                                   |
|--|--------------|-----------------------------------|
| Design   | BE           | With lose center lip ring         |
| Bore type                                      | K            | Tapered, taper 1:12               |
| Cage   | JPA          | Sheet metal cage                  |
| Radial internal clearance                      | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication facility                         | Standard     |                                   |
| Spherical roller bearing for vibrating screens | T41A         | For vibrating screens             |

## Main Dimensions &amp; Performance Data

|          |             |                                   |
|----------|-------------|-----------------------------------|
| d        | 200 mm      | Bore diameter                     |
| D        | 420 mm      | Outside diameter                  |
| B        | 138 mm      | Width                             |
| $C_r$    | 2.440.000 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 2.950.000 N | Basic static load rating, radial  |
| $C_{ur}$ | 232.000 N   | Fatigue load limit, radial        |
| $n_G$    | 1.830 1/min | Limiting speed                    |
| $n_{gr}$ | 1.080 1/min | Reference speed                   |
| $m$      | 89,55 kg    | Weight                            |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 220 mm | Minimum diameter shaft shoulder       |
| $d_{a \max}$ | 240 mm | Maximum diameter of shaft shoulder    |
| $D_{a \max}$ | 400 mm | Maximum diameter of housing shoulder  |
| $r_{a \max}$ | 4 mm   | Maximum recess radius                 |
| $d_{b \min}$ | 216 mm | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 10 mm  | Minimum cavity width of the sleeve    |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 5 mm     | Minimum chamfer dimension          |
| $D_1$      | 355,1 mm | Bore diameter outer ring           |
| $d_2$      | 248,8 mm | Raceway diameter of the inner ring |
| $d_s$      | 12,5 mm  | Diameter lubrication hole          |
| $n_s$      | 23,5 mm  | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |  |
|-------|------|--|
| $e$   | 0,34 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 1,98 | Dynamic axial load factor  |
| $Y_2$ | 2,94 | Dynamic axial load factor  |
| $Y_0$ | 1,93 | Static axial load factor   |

### Additional information

|        |                   |
|--------|-------------------|
| H2340  | Adapter sleeve    |
| AH2340 | Withdrawal sleeve |



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment