



FAG

**23140-BE-XL-C2**

Spherical Roller Bearing

Spherical roller bearing 231...-BE-XL,  
symmetric with rib washer

X-life

## Technical information



## Your current product variant

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C2 (Group 2)	Internal clearance smaller than CN
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	200 mm	Bore diameter
D	340 mm	Outside diameter
B	112 mm	Width
$C_r$	1.610.000 N	Basic dynamic load rating, radial
$C_{0r}$	2.270.000 N	Basic static load rating, radial
$C_{ur}$	193.000 N	Fatigue load limit, radial
$n_G$	2.040 1/min	Limiting speed
$n_{gr}$	1.230 1/min	Reference speed
$\approx m$	40,32 kg	Weight



### Mounting dimensions

$d_{a \min}$	214 mm	Minimum diameter shaft shoulder
$D_{a \max}$	326 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	295,8 mm	Bore diameter outer ring
$d_2$	230,4 mm	Raceway diameter of the inner ring
$d_s$	9,5 mm	Diameter lubrication hole
$n_s$	17,7 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,32	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,1	Dynamic axial load factor
$Y_2$	3,13	Dynamic axial load factor
$Y_0$	2,06	Static axial load factor



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment