


Technical information



Your current product variant

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	400 mm	Outside diameter
B	140 mm	Width
C_r	2.210.000 N	Basic dynamic load rating, radial
C_{0r}	3.650.000 N	Basic static load rating, radial
C_{ur}	345.000 N	Fatigue load limit, radial
n_G	1.510 1/min	Limiting speed
n_{gr}	880 1/min	Reference speed
$\approx m$	62,845 kg	Weight



Mounting dimensions

$d_{a \min}$	274,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	385,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
D_1	349 mm	Bore diameter outer ring
d_2	288,3 mm	Raceway diameter of the inner ring
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,09	Dynamic axial load factor
Y_2	3,11	Dynamic axial load factor
Y_0	2,04	Static axial load factor



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment