



FAG

24034-BE-XL-K30-C2

Spherical Roller Bearing

Spherical roller bearings 240..-BE-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Technical information



Your current product variant

| | | |
|---------------------------|--------------|------------------------------------|
| Design | BE | With lose center lip ring |
| Bore type | K30 | Tapered, taper 1:30 |
| Cage | JPB | Sheet metal cage |
| Radial internal clearance | C2 (Group 2) | Internal clearance smaller than CN |
| Relubrication facility | Standard | |

Main Dimensions & Performance Data

| | | |
|-------------|-------------|-----------------------------------|
| d | 170 mm | Bore diameter |
| D | 260 mm | Outside diameter |
| B | 90 mm | Width |
| C_r | 940.000 N | Basic dynamic load rating, radial |
| C_{0r} | 1.480.000 N | Basic static load rating, radial |
| C_{ur} | 162.000 N | Fatigue load limit, radial |
| n_G | 2.380 1/min | Limiting speed |
| n_{gr} | 1.540 1/min | Reference speed |
| $\approx m$ | 16,709 kg | Weight |



Mounting dimensions

| | | |
|--------------|----------|--------------------------------------|
| $d_{a \min}$ | 180,2 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 249,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,1 mm | Maximum recess radius |

Dimensions

| | | |
|------------|----------|------------------------------------|
| r_{\min} | 2,1 mm | Minimum chamfer dimension |
| D_1 | 228,4 mm | Bore diameter outer ring |
| d_2 | 190 mm | Raceway diameter of the inner ring |
| d_s | 4,8 mm | Diameter lubrication hole |
| n_s | 9,5 mm | Width of lubricating groove |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0,31 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 2,2 | Dynamic axial load factor |
| Y_2 | 3,27 | Dynamic axial load factor |
| Y_0 | 2,15 | Static axial load factor |

Additional information

| | |
|---------|-------------------|
| AH24034 | Withdrawal sleeve |
|---------|-------------------|



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment