


## Technical information



### Your current product variant

Design	BE	With lose center lip ring
Bore type	K30	Tapered, taper 1:30
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication facility	Standard	

### Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	420 mm	Outside diameter
B	140 mm	Width
$C_r$	2.290.000 N	Basic dynamic load rating, radial
$C_{0r}$	3.950.000 N	Basic static load rating, radial
$C_{ur}$	370.000 N	Fatigue load limit, radial
$n_G$	1.420 1/min	Limiting speed
$n_{gr}$	800 1/min	Reference speed
$\approx m$	66,11 kg	Weight



### Mounting dimensions

$d_{a \min}$	294,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	405,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$D_1$	370,5 mm	Bore diameter outer ring
$d_2$	310,3 mm	Raceway diameter of the inner ring
$d_s$	6,3 mm	Diameter lubrication hole
$n_s$	12,2 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,3	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,23	Dynamic axial load factor
$Y_2$	3,32	Dynamic axial load factor
$Y_0$	2,18	Static axial load factor

### Additional information

AH24056

Withdrawal sleeve



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment