



FAG

24172-BE-XL-K30-C4

Spherical Roller Bearing

Spherical roller bearings 241...-BE-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Technical information



Your current product variant

| | | |
|---------------------------|--------------|-----------------------------------|
| Design | BE | With lose center lip ring |
| Bore type | K30 | Tapered, taper 1:30 |
| Cage | JPB | Sheet metal cage |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication | Standard | |

Main Dimensions & Performance Data

| | | |
|----------|-------------|-----------------------------------|
| d | 360 mm | Bore diameter |
| D | 600 mm | Outside diameter |
| B | 243 mm | Width |
| C_r | 5.600.000 N | Basic dynamic load rating, radial |
| C_{0r} | 9.100.000 N | Basic static load rating, radial |
| C_{ur} | 680.000 N | Fatigue load limit, radial |
| n_G | 890 1/min | Limiting speed |
| n_{gr} | 350 1/min | Reference speed |
| m | 263 kg | Weight |



Mounting dimensions

| | | |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 380 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 580 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 4 mm | Maximum recess radius |

Dimensions

| | | |
|------------|----------|------------------------------------|
| r_{\min} | 5 mm | Minimum chamfer dimension |
| D_1 | 505,9 mm | Bore diameter outer ring |
| d_2 | 399,4 mm | Raceway diameter of the inner ring |
| d_s | 9,5 mm | Diameter lubrication hole |
| n_s | 17,7 mm | Width of lubricating groove |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0,4 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 1,69 | Dynamic axial load factor |
| Y_2 | 2,52 | Dynamic axial load factor |
| Y_0 | 1,65 | Static axial load factor |

Additional information

| | |
|-----------|-------------------|
| AH24172-H | Withdrawal sleeve |
|-----------|-------------------|



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment