View product details on medias

01.06.2026, 16:05:49 UTC

SCHAEFFLER



FAG

X-life

22217-E1-XL-K-C4

Spherical Roller Bearing

Spherical roller bearings 222..-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

Technical information



Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	JPA	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	Standard	



Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	36 mm	Width
C_r	305.000 N	Basic dynamic load rating, radial
C_{0r}	325.000 N	Basic static load rating, radial
C_{ur}	39.000 N	Fatigue load limit, radial
n_G	5.700 1/min	Limiting speed
$n_{\vartheta r}$	3.450 1/min	Reference speed
≈m	2,546 kg	Weight

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Mounting dimensions

$d_{a\ min}$	96 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	99 mm	Maximum diameter of shaft shoulder
$D_{a\ max}$	139 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2 mm	Maximum recess radius
$d_{b\ min}$	91 mm	Minimum cavity diameter of the sleeve
$B_{a\ min}$	12 mm	Minimum cavity width of the sleeve

Dimensions

r_{min}	2 mm	Minimum chamfer dimension
D_1	135,4 mm	Bore diameter outer ring
d_2	99,7 mm	Raceway diameter of the inner ring
d_s	3,2 mm	Diameter lubrication hole
n_s	6,5 mm	Width of lubricating groove

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,22	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y_1	3,04	Dynamic axial load factor
Y_2	4,53	Dynamic axial load factor
Y_0	2,97	Static axial load factor

Additional information

	H317	Adapter sleeve
	AHX317	Withdrawal sleeve

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Characteristics

Radial load

Axial load in one direction

Axial load in two directions

Grease Lubrication

Oil Lubrication

Not sealed

Static angular error and misalignment

Dynamic angular error and misalignment

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form