



## Technical information



### Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	JPA	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

### Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	100 mm	Outside diameter
B	36 mm	Width
$C_r$	187.000 N	Basic dynamic load rating, radial
$C_{0r}$	183.000 N	Basic static load rating, radial
$C_{ur}$	16.500 N	Fatigue load limit, radial
$n_G$	6.800 1/min	Limiting speed
$n_{gr}$	5.000 1/min	Reference speed
$m$	1,34 kg	Weight



### Mounting dimensions

$d_{a \min}$	54 mm	Minimum diameter shaft shoulder
$d_{a \max}$	58 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	91 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum recess radius
$d_{b \min}$	50 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	5 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	84,7 mm	Bore diameter outer ring
$d_2$	58,9 mm	Raceway diameter of the inner ring
$d_s$	3,2 mm	Diameter lubrication hole
$n_s$	6,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,36	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	1,9	Dynamic axial load factor
$Y_2$	2,83	Dynamic axial load factor
$Y_0$	1,86	Static axial load factor

### Additional information

H2309	Adapter sleeve
AH2309	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment