

**FAG****22224-E1A-XL-M-H40-C4**

Spherical Roller Bearing

Spherical roller bearing 222...-E1A-XL-M-H40,
symmetric 2 outer ribs**X-life**

Technical information

**Your current product variant**

Design	E1A	Without central rip
Bore type	Z	Cylindrical
Cage	M	Brass Cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	H40	Without lubricating groove and holes

**Main Dimensions & Performance Data**

d	120 mm	Bore diameter
D	215 mm	Outside diameter
B	58 mm	Width
C_r	640.000 N	Basic dynamic load rating, radial
C_{0r}	740.000 N	Basic static load rating, radial
C_{ur}	70.000 N	Fatigue load limit, radial
n_G	3.650 1/min	Limiting speed
n_{gr}	2.700 1/min	Reference speed
$\approx m$	8,85 kg	Weight

Mounting dimensions

$d_{a \min}$	132 mm	Minimum diameter shaft shoulder
$D_{a \max}$	203 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	192 mm	Bore diameter outer ring
d_2	141,9 mm	Raceway diameter of the inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,25	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,71	Dynamic axial load factor
Y_2	4,04	Dynamic axial load factor
Y_0	2,65	Static axial load factor