

**FAG****22326-E1A-XL-K-M**

Spherical Roller Bearing

Spherical roller bearing 223...-E1A-XL-K-M,
symmetric 2 outer ribs**X-life**

Technical information



Your current product variant

| | | |
|---------------------------|--------------|---------------------------|
| Design | E1A | Without central rip |
| Bore type | K | Tapered, taper 1:12 |
| Cage | M | Brass Cage |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication facility | Standard | |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 130 mm | Bore diameter |
| D | 280 mm | Outside diameter |
| B | 93 mm | Width |
| C _r | 1.250.000 N | Basic dynamic load rating, radial |
| C _{0r} | 1.370.000 N | Basic static load rating, radial |
| C _{ur} | 120.000 N | Fatigue load limit, radial |
| n _G | 2.650 1/min | Limiting speed |
| n _{gr} | 1.820 1/min | Reference speed |
| m | 26,566 kg | Weight |



Mounting dimensions

| | | |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 147 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 263 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 3 mm | Maximum recess radius |
| $d_{a \max}$ | 162 mm | Maximum diameter of shaft shoulder |
| $d_{b \min}$ | 142 mm | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 8 mm | Minimum cavity width of the sleeve |

Dimensions

| | | |
|------------|----------|------------------------------------|
| r_{\min} | 4 mm | Minimum chamfer dimension |
| D_1 | 239,5 mm | Bore diameter outer ring |
| d_2 | 162,2 mm | Raceway diameter of the inner ring |
| d_s | 9,5 mm | Diameter lubrication hole |
| n_s | 17,7 mm | Width of lubricating groove |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0,33 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 2,06 | Dynamic axial load factor |
| Y_2 | 3,06 | Dynamic axial load factor |
| Y_0 | 2,01 | Static axial load factor |

Additional information

| | |
|----------|-------------------|
| H2326 | Adapter sleeve |
| AHX2326G | Withdrawal sleeve |