

**FAG****22324-E1A-XL-K-MA-T41A**

Spherical Roller Bearing

Spherical roller bearing 223..-E1A-XL-K-MA-T41A, symmetric 2 outer ribs

**X-life**

## Technical information

**Your current product variant**

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	MA	Solid brass cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	Standard	
Spherical roller bearing for vibrating screens	T41A	For vibrating screens

**Main Dimensions & Performance Data**

d	120 mm	Bore diameter
D	260 mm	Outside diameter
B	86 mm	Width
C <sub>r</sub>	1.080.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.170.000 N	Basic static load rating, radial
C <sub>ur</sub>	105.000 N	Fatigue load limit, radial
n <sub>G</sub>	2.850 1/min	Limiting speed
n <sub>gr</sub>	2.000 1/min	Reference speed
m	22,153 kg	Weight



### Mounting dimensions

$d_{a \min}$	134 mm	Minimum diameter shaft shoulder
$D_{a \max}$	246 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$d_{a \max}$	150 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	131 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	222,4 mm	Bore diameter outer ring
$d_2$	150,7 mm	Raceway diameter of the inner ring
$d_s$	8 mm	Diameter lubrication hole
$n_s$	15 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,33	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,06	Dynamic axial load factor
$Y_2$	3,06	Dynamic axial load factor
$Y_0$	2,01	Static axial load factor

### Additional information

H2324	Adapter sleeve
AHX2324G	Withdrawal sleeve