



FAG

**22311-E1A-XL-MA-T41A** [🔗](#)

Spherical Roller Bearing

Spherical roller bearing 223..-E1A-XL-MA-T41A, symmetric 2 outer ribs

X-life

## Technical information



## Your current product variant

Design	E1A	Without central rip
Bore type	Z	Cylindrical
Cage	MA	Solid brass cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication	Standard	
Spherical roller bearing for vibrating screens	T41A	For vibrating screens

## Main Dimensions &amp; Performance Data

d	55 mm	Bore diameter
D	120 mm	Outside diameter
B	43 mm	Width
C <sub>r</sub>	265.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	260.000 N	Basic static load rating, radial
C <sub>ur</sub>	24.600 N	Fatigue load limit, radial
n <sub>G</sub>	5.800 1/min	Limiting speed
n <sub>gr</sub>	4.500 1/min	Reference speed
m	2,41 kg	Weight



### Mounting dimensions

$d_{a \min}$	66 mm	Minimum diameter shaft shoulder
$D_{a \max}$	109 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum recess radius

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	101,4 mm	Bore diameter outer ring
$d_2$	68,9 mm	Raceway diameter of the inner ring
$d_s$	3,2 mm	Diameter lubrication hole
$n_s$	6,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,36	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	1,89	Dynamic axial load factor
$Y_2$	2,81	Dynamic axial load factor
$Y_0$	1,84	Static axial load factor