

**FAG****23034-E1A-XL-K-M-H40-C3**

Spherical Roller Bearing

Spherical roller bearing 230..-E1A-XL-K-M-H40, symmetric 2 outer ribs

X-life

Technical information



Your current product variant

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication facility	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	260 mm	Outside diameter
B	67 mm	Width
C _r	880.000 N	Basic dynamic load rating, radial
C _{0r}	1.230.000 N	Basic static load rating, radial
C _{ur}	151.000 N	Fatigue load limit, radial
n _G	2.800 1/min	Limiting speed
n _{gr}	1.890 1/min	Reference speed
m	12,353 kg	Weight



Mounting dimensions

$d_{a \min}$	180,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	249,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
$d_{a \max}$	189 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	179 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	8 mm	Minimum cavity width of the sleeve

Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	237,2 mm	Bore diameter outer ring
d_2	189,8 mm	Raceway diameter of the inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,98	Dynamic axial load factor
Y_2	4,44	Dynamic axial load factor
Y_0	2,92	Static axial load factor

Additional information

H3034	Adapter sleeve
AH3034	Withdrawal sleeve



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment