

**FAG****23120-E1A-XL-K-M-C3**

## Spherical Roller Bearing

Spherical roller bearings 231...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

**X-life**

## Technical information



## Your current product variant

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	
Special material	Standard	

## Main Dimensions &amp; Performance Data

d	100 mm	Bore diameter
D	165 mm	Outside diameter
B	52 mm	Width
C <sub>r</sub>	450.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	570.000 N	Basic static load rating, radial
C <sub>ur</sub>	54.000 N	Fatigue load limit, radial
n <sub>G</sub>	4.000 1/min	Limiting speed
n <sub>gr</sub>	2.750 1/min	Reference speed
≈m	4,38 kg	Weight



### Mounting dimensions

$d_{a \min}$	111 mm	Minimum diameter shaft shoulder
$D_{a \max}$	154 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum recess radius
$d_{a \max}$	115 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	107 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	146,3 mm	Bore diameter outer ring
$d_s$	3,2 mm	Diameter lubrication hole
$n_s$	6,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,28	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,37	Dynamic axial load factor
$Y_2$	3,53	Dynamic axial load factor
$Y_0$	2,32	Static axial load factor

### Additional information

H3120	Adapter sleeve
AHX3120	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment