

**FAG****23230-E1A-XL-M-H40-C3**

Spherical Roller Bearing

Spherical roller bearing 232...-E1A-XL-M-H40,
symmetric 2 outer ribs**X-life**

Technical information

**Your current product variant**

Design	E1A	Without central rip
Bore type	Z	Cylindrical
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication facility	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	270 mm	Outside diameter
B	96 mm	Width
C_r	1.280.000 N	Basic dynamic load rating, radial
C_{0r}	1.660.000 N	Basic static load rating, radial
C_{ur}	133.000 N	Fatigue load limit, radial
n_G	2.400 1/min	Limiting speed
n_{gr}	1.400 1/min	Reference speed
$\approx m$	23,7 kg	Weight

**Mounting dimensions**

$d_{a \min}$	164 mm	Minimum diameter shaft shoulder
$D_{a \max}$	256 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius



Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	232,6 mm	Bore diameter outer ring









Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,02	Dynamic axial load factor
Y_2	3	Dynamic axial load factor
Y_0	1,97	Static axial load factor

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment