



FAG

**23176-BEA-XL-K-MB1-C2**

Spherical Roller Bearing

Spherical roller bearing 231...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

## Technical information



## Your current product variant

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	C2 (Group 2)	Internal clearance smaller than CN
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	380 mm	Bore diameter
D	620 mm	Outside diameter
B	194 mm	Width
$C_r$	4.700.000 N	Basic dynamic load rating, radial
$C_{0r}$	7.600.000 N	Basic static load rating, radial
$C_{ur}$	540.000 N	Fatigue load limit, radial
$n_G$	990 1/min	Limiting speed
$n_{gr}$	530 1/min	Reference speed
$m$	221 kg	Weight



### Mounting dimensions

$d_{a \min}$	400 mm	Minimum diameter shaft shoulder
$D_{a \max}$	600 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$d_{a \max}$	436 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	401 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	15 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$D_1$	543,6 mm	Bore diameter outer ring
$d_s$	12,5 mm	Diameter lubrication hole
$n_s$	23,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,3	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,25	Dynamic axial load factor
$Y_2$	3,34	Dynamic axial load factor
$Y_0$	2,2	Static axial load factor

### Additional information

H3176-HG	Adapter sleeve
AH3176G-H	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment