



FAG

**23252-BEA-XL-K-MB1-C2**

## Spherical Roller Bearing

Spherical roller bearing 232...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

## Technical information



## Your current product variant

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	C2 (Group 2)	Internal clearance smaller than CN
Relubrication	Standard	

## Main Dimensions &amp; Performance Data

d	260 mm	Bore diameter
D	480 mm	Outside diameter
B	174 mm	Width
$C_r$	3.350.000 N	Basic dynamic load rating, radial
$C_{0r}$	4.750.000 N	Basic static load rating, radial
$C_{ur}$	370.000 N	Fatigue load limit, radial
$n_G$	1.360 1/min	Limiting speed
$n_{gr}$	690 1/min	Reference speed
$m$	133,45 kg	Weight



### Mounting dimensions

$d_{a \min}$	280 mm	Minimum diameter shaft shoulder
$D_{a \max}$	460 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$d_{a \max}$	309 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	278 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	2 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$D_1$	404,3 mm	Bore diameter outer ring
$d_s$	12,5 mm	Diameter lubrication hole
$n_s$	23,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,36	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	1,87	Dynamic axial load factor
$Y_2$	2,79	Dynamic axial load factor
$Y_0$	1,83	Static axial load factor

### Additional information

H2352X	Adapter sleeve
AH2352G	Withdrawal sleeve



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment