

FAG



24084-BEA-XL-K30-MB1

Spherical Roller Bearing

Spherical roller bearings 240...-BEA-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Technical information



Your current product variant

Design	BEA	With lose center lip ring
Bore type	K30	Tapered, taper 1:30
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	420 mm	Bore diameter
D	620 mm	Outside diameter
B	200 mm	Width
C_r	4.600.000 N	Basic dynamic load rating, radial
C_{0r}	8.500.000 N	Basic static load rating, radial
C_{ur}	720.000 N	Fatigue load limit, radial
n_G	890 1/min	Limiting speed
n_{gr}	465 1/min	Reference speed
$\approx m$	202,5 kg	Weight

Mounting dimensions

$d_{a \min}$	438 mm	Minimum diameter shaft shoulder
$D_{a \max}$	602 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius



Dimensions

r_{\min}	5 mm	Minimum chamfer dimension
D_1	529,4 mm	Bore diameter outer ring
d_s	12,5 mm	Diameter lubrication hole
n_s	23,5 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,29	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,32	Dynamic axial load factor
Y_2	3,45	Dynamic axial load factor
Y_0	2,26	Static axial load factor

Additional information

AH24080-H

Withdrawal sleeve

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment