


**FAG****230/710-B-K-MB**

Spherical Roller Bearing

Spherical roller bearing 230..-B-K-MB,
symmetric 3 ribs

Technical information



Your current product variant

Design	B	With fixed central rib
Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	710 mm	Bore diameter
D	1.030 mm	Outside diameter
B	236 mm	Width
C_r	7.600.000 N	Basic dynamic load rating, radial
C_{0r}	16.900.000 N	Basic static load rating, radial
C_{ur}	1.180.000 N	Fatigue load limit, radial
n_G	590 1/min	Limiting speed
n_{gr}	325 1/min	Reference speed
m	644 kg	Weight



Mounting dimensions

$d_{a \min}$	738 mm	Minimum diameter shaft shoulder
$D_{a \max}$	1.002 mm	Maximum diameter of housing shoulder
$r_{a \max}$	6 mm	Maximum recess radius
$d_{a \max}$	785 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	735 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	23 mm	Minimum cavity width of the sleeve

Dimensions

r_{\min}	7,5 mm	Minimum chamfer dimension
D_1	938,8 mm	Bore diameter outer ring
d_s	12,5 mm	Diameter lubrication hole
n_s	23,5 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,22	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,07	Dynamic axial load factor
Y_2	4,57	Dynamic axial load factor
Y_0	3	Static axial load factor

Additional information

H30/710-HG	Adapter sleeve
AH30/710A-H	Withdrawal sleeve



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment