**FAG****230/670-B-MB**

Spherical Roller Bearing

Spherical roller bearing 230..-B-MB,
symmetric 3 ribs

Technical information



Your current product variant


Design	B	With fixed central rib
Bore type	Z	Cylindrical
Cage	MB	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	670 mm	Bore diameter
D	980 mm	Outside diameter
B	230 mm	Width
C_r	7.200.000 N	Basic dynamic load rating, radial
C_{0r}	15.800.000 N	Basic static load rating, radial
C_{ur}	1.120.000 N	Fatigue load limit, radial
n_G	630 1/min	Limiting speed
n_{gr}	350 1/min	Reference speed
$\approx m$	600 kg	Weight

Mounting dimensions

$d_{a \min}$	698 mm	Minimum diameter shaft shoulder
$D_{a \max}$	952 mm	Maximum diameter of housing shoulder
$r_{a \max}$	6 mm	Maximum recess radius





Dimensions

r_{\min}	7,5 mm	Minimum chamfer dimension
D_1	888,7 mm	Bore diameter outer ring
d_s	12,5 mm	Diameter lubrication hole
n_s	23,5 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,22	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,01	Dynamic axial load factor
Y_2	4,48	Dynamic axial load factor
Y_0	2,94	Static axial load factor

Characteristics



Large bearing