

**FAG****239/1180-B-K-MB**

Spherical Roller Bearing

Spherical roller bearings 239...-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

Technical information



Your current product variant


Design	B	With fixed central rib
Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication	Standard	

Main Dimensions & Performance Data

d	1.180 mm	Bore diameter
D	1.540 mm	Outside diameter
B	272 mm	Width
C _r	11.300.000 N	Basic dynamic load rating, radial
C _{0r}	31.000.000 N	Basic static load rating, radial
C _{ur}	1.810.000 N	Fatigue load limit, radial
n _G	370 1/min	Limiting speed
n _{gr}	177 1/min	Reference speed
m	1.320 kg	Weight

Mounting dimensions

d _{a min}	1.208 mm	Minimum diameter shaft shoulder
D _{a max}	1.512 mm	Maximum diameter of housing shoulder
r _{a max}	6 mm	Maximum recess radius





Dimensions

r_{\min}	7,5 mm	Minimum chamfer dimension
D_1	1.438,3 mm	Bore diameter outer ring
d_s	12,5 mm	Diameter lubrication hole
n_s	23,5 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,17	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	4,05	Dynamic axial load factor
Y_2	6,04	Dynamic axial load factor
Y_0	3,96	Static axial load factor

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing
	Static angular error and misalignment
	Dynamic angular error and misalignment