


**FAG****239/900-K-MB**

## Spherical Roller Bearing

Spherical roller bearing 239..-K-MB,  
symmetric 3 ribs

## Technical information



## Your current product variant

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	900 mm	Bore diameter
D	1.180 mm	Outside diameter
B	206 mm	Width
$C_r$	6.500.000 N	Basic dynamic load rating, radial
$C_{0r}$	17.200.000 N	Basic static load rating, radial
$C_{ur}$	1.030.000 N	Fatigue load limit, radial
$n_G$	520 1/min	Limiting speed
$n_{gr}$	260 1/min	Reference speed
$m$	598 kg	Weight

## Mounting dimensions

$d_{a \min}$	923 mm	Minimum diameter shaft shoulder
$D_{a \max}$	1.157 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum recess radius
$d_{a \max}$	972 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	923 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	27 mm	Minimum cavity width of the sleeve



### Dimensions

$r_{\min}$	6 mm	Minimum chamfer dimension
$D_1$	1.098,8 mm	Bore diameter outer ring
$d_s$	12,5 mm	Diameter lubrication hole
$n_s$	23,5 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,16	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	4,28	Dynamic axial load factor
$Y_2$	6,37	Dynamic axial load factor
$Y_0$	4,19	Static axial load factor

### Additional information

H39/900-HG	Adapter sleeve
AH39/900-H	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment