


**FAG****23948-K-MB-C3** [↗](#)

Spherical Roller Bearing

Spherical roller bearing 239..-K-MB,
symmetric 3 ribs

Technical information

**Your current product variant**

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	320 mm	Outside diameter
B	60 mm	Width
C_r	640.000 N	Basic dynamic load rating, radial
C_{0r}	1.370.000 N	Basic static load rating, radial
C_{ur}	96.000 N	Fatigue load limit, radial
n_G	2.440 1/min	Limiting speed
n_{gr}	1.310 1/min	Reference speed
$\approx m$	12,935 kg	Weight

Mounting dimensions

$d_{a \min}$	250,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	309,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
$d_{a \max}$	261 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	250 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	11 mm	Minimum cavity width of the sleeve



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	297,8 mm	Bore diameter outer ring
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,17	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	4,05	Dynamic axial load factor
Y_2	6,04	Dynamic axial load factor
Y_0	3,96	Static axial load factor

Additional information

H3948	Adapter sleeve
AH3948	Withdrawal sleeve



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment