


**FAG****23968-K-MB**

Spherical Roller Bearing

Spherical roller bearing 239..-K-MB,
symmetric 3 ribs

Technical information



Your current product variant

| | | |
|---------------------------|--------------|---------------------------|
| Bore type | K | Tapered, taper 1:12 |
| Cage | MB | Solid brass cage |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication facility | Standard | |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 340 mm | Bore diameter |
| D | 460 mm | Outside diameter |
| B | 90 mm | Width |
| C _r | 1.370.000 N | Basic dynamic load rating, radial |
| C _{0r} | 3.000.000 N | Basic static load rating, radial |
| C _{ur} | 204.000 N | Fatigue load limit, radial |
| n _G | 1.610 1/min | Limiting speed |
| n _{gr} | 860 1/min | Reference speed |
| m | 41,68 kg | Weight |

Mounting dimensions

| | | |
|--------------------|----------|--------------------------------------|
| d _{a min} | 352,4 mm | Minimum diameter shaft shoulder |
| D _{a max} | 447,6 mm | Maximum diameter of housing shoulder |
| r _{a max} | 2,5 mm | Maximum recess radius |



Dimensions

| | | |
|------------|----------|-----------------------------|
| r_{\min} | 3 mm | Minimum chamfer dimension |
| D_1 | 426,7 mm | Bore diameter outer ring |
| d_s | 9,5 mm | Diameter lubrication hole |
| n_s | 17,7 mm | Width of lubricating groove |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0,18 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 3,85 | Dynamic axial load factor |
| Y_2 | 5,73 | Dynamic axial load factor |
| Y_0 | 3,76 | Static axial load factor |

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |
|  | Large bearing |
|  | Static angular error and misalignment |
|  | Dynamic angular error and misalignment |