

**FAG****23944-S-MB-C3**

Spherical Roller Bearing

Spherical roller bearings 239, main dimensions to DIN 635-2

Technical information

**Your current product variant**

Bore type	Z	Cylindrical
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	S	With 3 lubricating holes and groove

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	300 mm	Outside diameter
B	60 mm	Width
C_r	610.000 N	Basic dynamic load rating, radial
C_{0r}	1.240.000 N	Basic static load rating, radial
C_{ur}	74.000 N	Fatigue load limit, radial
n_G	2.600 1/min	Limiting speed
n_{gr}	1.460 1/min	Reference speed
m	12,4 kg	Weight

Mounting dimensions

$d_{a \min}$	230,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	289,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	277,4 mm	Bore diameter outer ring
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,18	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,76	Dynamic axial load factor
Y_2	5,59	Dynamic axial load factor
Y_0	3,67	Static axial load factor

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment
	Dynamic angular error and misalignment