

**FAG****22212-E1-XL-C3>A**

Spherical Roller Bearing

Spherical roller bearings 222...-E1, main dimensions to DIN 635-2

X-life

Technical information

**Your current product variant**

| | | |
|---------------------------|--------------|-----------------------------------|
| Design | E1 | Without central rip |
| Bore type | Z | Cylindrical |
| Cage | JPA | Sheet metal cage |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication facility | Standard | |

Main Dimensions & Performance Data

| | | |
|-------------|-------------|-----------------------------------|
| d | 60 mm | Bore diameter |
| D | 110 mm | Outside diameter |
| B | 28 mm | Width |
| C_r | 160.000 N | Basic dynamic load rating, radial |
| C_{0r} | 155.000 N | Basic static load rating, radial |
| C_{ur} | 20.700 N | Fatigue load limit, radial |
| n_G | 8.100 1/min | Limiting speed |
| n_{gr} | 4.550 1/min | Reference speed |
| $\approx m$ | 1,098 kg | Weight |

Mounting dimensions

| | | |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 69 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 101 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,5 mm | Maximum recess radius |



Dimensions

| | | |
|------------|---------|------------------------------------|
| r_{\min} | 1,5 mm | Minimum chamfer dimension |
| D_1 | 98,7 mm | Bore diameter outer ring |
| d_2 | 71,6 mm | Raceway diameter of the inner ring |
| d_s | 3,2 mm | Diameter lubrication hole |
| n_s | 6,5 mm | Width of lubricating groove |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0,23 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 2,98 | Dynamic axial load factor |
| Y_2 | 4,44 | Dynamic axial load factor |
| Y_0 | 2,92 | Static axial load factor |

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment