



FAG

**23038-E1A-XL-K-M-C5**

## Spherical Roller Bearing

Spherical roller bearings 230..-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

## Technical information



## Your current product variant

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Relubrication facility	Standard	
Special material	Standard	

## Main Dimensions &amp; Performance Data

d	190 mm	Bore diameter
D	290 mm	Outside diameter
B	75 mm	Width
C <sub>r</sub>	1.080.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.550.000 N	Basic static load rating, radial
C <sub>ur</sub>	183.000 N	Fatigue load limit, radial
n <sub>G</sub>	2.490 1/min	Limiting speed
n <sub>gr</sub>	1.660 1/min	Reference speed
m	18,2 kg	Weight



### Mounting dimensions

$d_{a \min}$	200,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	279,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
$d_{a \max}$	211 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	199 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	9 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	264,5 mm	Bore diameter outer ring
$d_s$	8 mm	Diameter lubrication hole
$n_s$	15 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,23	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,98	Dynamic axial load factor
$Y_2$	4,44	Dynamic axial load factor
$Y_0$	2,92	Static axial load factor

### Additional information

H3038	Adapter sleeve
AH3038G	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment