



FAG

**23128-E1A-XL-M>A**

Spherical Roller Bearing

Spherical roller bearings 231...-E1A, main dimensions to DIN 635-2

X-life

## Technical information




## Your current product variant

Design	E1A	Without central rip
Bore type	Z	Cylindrical
Cage	M	Brass Cage
Relubrication	Standard	

## Main Dimensions &amp; Performance Data

d	140 mm	Bore diameter
D	225 mm	Outside diameter
B	68 mm	Width
$C_r$	760.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.010.000 N	Basic static load rating, radial
$C_{ur}$	90.000 N	Fatigue load limit, radial
$n_G$	3.000 1/min	Limiting speed
$n_{gr}$	1.930 1/min	Reference speed
$m$	10,272 kg	Weight



## Mounting dimensions

$d_{a \min}$	152 mm	Minimum diameter shaft shoulder
$D_{a \max}$	213 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius



## Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	201 mm	Bore diameter outer ring
$d_s$	4,8 mm	Diameter lubrication hole
$n_s$	9,5 mm	Width of lubricating groove

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

## Calculation factors

$e$	0,27	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,49	Dynamic axial load factor
$Y_2$	3,71	Dynamic axial load factor
$Y_0$	2,43	Static axial load factor

## Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Static angular error and misalignment
	Dynamic angular error and misalignment