

**FAG****23228-E1A-XL-K-M-C3>A**

## Spherical Roller Bearing

Spherical roller bearings 232...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

**X-life**

## Technical information



## Your current product variant

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	

## Main Dimensions &amp; Performance Data

d	140 mm	Bore diameter
D	250 mm	Outside diameter
B	88 mm	Width
C <sub>r</sub>	1.090.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.400.000 N	Basic static load rating, radial
C <sub>ur</sub>	116.000 N	Fatigue load limit, radial
n <sub>G</sub>	2.600 1/min	Limiting speed
n <sub>gr</sub>	1.550 1/min	Reference speed
m	18 kg	Weight



### Mounting dimensions

$d_{a \min}$	154 mm	Minimum diameter shaft shoulder
$D_{a \max}$	236 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$d_{a \max}$	162 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	152 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	22 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	216 mm	Bore diameter outer ring
$d_s$	6,3 mm	Diameter lubrication hole
$n_s$	12,2 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,33	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,04	Dynamic axial load factor
$Y_2$	3,04	Dynamic axial load factor
$Y_0$	2	Static axial load factor

### Additional information

H2328	Adapter sleeve
AHX3228G	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment